

§ 200.948

standard C-578-92, Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation.

(2) This standard has been approved by the Director of the Federal Register for incorporation by reference. The standard is available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103. This standard is also available for inspection at the Office of the Federal Register, 800 North Capitol Street, NW., 7th Floor, suite 700, Washington, DC.

(b) *Labeling.* Under the procedures set forth in § 200.935(d)(6) concerning labeling of a product, the administrator's certification of compliance with the applicable standards and the type of board are required to be on the certification label issued by the administrator to the manufacturer.

(c) *Periodic tests and quality assurance inspection.* Under the procedure set forth in § 200.935(d)(8), testing and inspection shall be conducted as follows:

(1) At least every six months, the administrator shall visit the manufacturer's facility to select a sample of each certified polystyrene foam insulation board for testing by a laboratory approved by the administrator.

(2) The administrator also shall review the quality assurance procedures every six months to assure that they are being followed by the manufacturer.

[58 FR 67675, Dec. 22, 1993]

§ 200.948 Building product standards and certification program for carpet cushion.

(a) *Applicable standards.* (1) All carpet cushion shall be designed, manufactured, and tested in compliance with the following standards from the American Society for Testing and Materials:

(i) ASTM D 1667-76—(Reapproved 1990) Standard Specification for Flexible Cellular Materials—Vinyl Chloride Polymers and Copolymers (Closed-Cell Foam);

(ii) ASTM D2646-87—Standard Test Methods for Backing Fabrics;

(iii) ASTM D629-88—Standard Test Methods for Quantitative Analysis of Textiles;

(iv) ASTM D3574-91—Standard Test Methods for Flexible Cellular Mate-

24 CFR Ch. II (4-1-00 Edition)

rials—Slab, Bonded, and Molded Urethane Foams;

(v) ASTM D3676-78—Standard Specification for Rubber Cellular Cushion Used for Carpet or Rug Underlay.

(2) These standards have been approved by the Director of the Federal Register for incorporation by reference. The standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103. These standards are also available for inspection at the Office of the Federal Register, 800 North Capitol Street, NW., 7th Floor, suite 700, Washington, DC.

(b) *Labeling.* Under the procedures set forth in § 200.935(d)(6) concerning labeling of a product, the administrator's validation mark, the manufacturer's certification of compliance with the applicable standards, and the type and class all are required to be on the certification label issued by the administrator to the manufacturer.

(c) *Periodic tests and quality assurance inspection.* Under the procedure set forth in § 200.935(d)(8), testing and inspection shall be conducted as follows:

(1) At least every six months, the administrator shall visit the manufacturer's facility to select a sample of each certified carpet cushion for testing by a laboratory approved by the administrator.

(2) The administrator also shall review the quality assurance procedures every six months to assure that they are being followed by the manufacturer.

[58 FR 67675, Dec. 22, 1993]

§ 200.949 Building product standards and certification program for exterior insulated steel door systems.

(a) *Applicable standards.* (1) All Exterior Insulated Steel Door Systems shall be designed, manufactured, and tested in compliance with the following standards from the American Society for Testing and Materials and Insulated Steel Door Systems Institute:

(i) ASTM A591/A591M-89—Standard Specification for Steel Sheet, Electrolytic-Zinc Coated, for Light Coating Mass Applications;